

# EKO FIT



## THE MOST FLEXIBLE SHELVING SYSTEM WITH SUPERIOR STRENGTH AND HYGIENE

- ⇒ **Superior strength**– high strength anodised aluminium load-bearing parts
- ⇒ **Superior hygiene**– removable polyethylene shelf slats for easy cleaning
- ⇒ **Quick and easy to assemble**– bolt free and no specialist tools required
- ⇒ **Fully adjustable**– shelf heights every 150mm
- ⇒ **Temperature resistant**- from  $-30^{\circ}\text{C}$  to  $+90^{\circ}\text{C}$
- ⇒ **Innovative design**– adaptable configurations using add-on units and corner supports
- ⇒ **Multi-purpose**– 330 size variations with single unit spans of up to 2000mm



[www.ezrshelving.com](http://www.ezrshelving.com)

## THE MOST FLEXIBLE SHELVING SYSTEM WITH SUPERIOR STRENGTH AND HYGIENE

### Shelf Loading (4-tier unit)

Length (mm)

	400-850	925-1000	1075-1225	1300-1450	1525-1675	1750-1825	1900	1975
<b>Linear</b>	250kg	240kg	220kg	200kg	180kg	150kg	120kg	110kg
<b>Angular</b>	180kg	170kg	150kg	140kg	120kg	100kg	85kg	75kg

### Pitch Levels

1550mm high unit

No. of shelves	3	4	5	6	7	8	9	10	11	12
<b>Floor to Bottom Shelf</b>	255mm	255mm	255mm	255mm	255mm	255mm	255mm	NA	NA	NA
<b>Between Shelves</b>	545mm	2x395mm 1x245mm	245mm	3x245mm 2x95mm	2x245mm 4x95mm	1x245mm 6x95mm	95mm	NA	NA	NA

1700mm high unit

<b>Floor to Bottom Shelf</b>	255mm	255mm	255mm	255mm	255mm	255mm	255mm	255mm	NA	NA
<b>Between Shelves</b>	1x695mm 1x545mm	395mm	1x395mm 3x245mm	4x245mm 1x95mm	3x245mm 3x95mm	2x245mm 5x95mm	1x245mm 7x95mm	95mm	NA	NA

2000mm high unit

<b>Floor to Bottom Shelf</b>	255mm	255mm	255mm	255mm	255mm	255mm	255mm	255mm	255mm	255mm
<b>Between Shelves</b>	1x845mm 1x695mm	2x545mm 1x395mm	3x395mm 1x245mm	1x395mm 4x245mm	5x245mm 1x95mm	4x245mm 3x95mm	3x245mm 5x95mm	2x245mm 7x95mm	1x245mm 9x95mm	95mm

### Cleaning Process

Shelf slats can be removed and cleaned in a dishwasher. Frames should be wiped clean with a dry cloth. If a damp clean is required, ensure the area is dried well. Do not use corrosive or abrasive cleaners on the frames.